

## **HIGH-SPEED SPIRAL DOOR, type “EFA-SST®-XXL Premium”**

Manufacture, delivery and installation of:

High-speed spiral door, type “EFA-SST®-XXL Premium”, with electro-mechanical high-performance door drive for permanent use for the most heavy-duty, industrial applications

The door system primarily consists of:

self-supporting steel side frames, steel parts (which are generally galvanised) and spiral-shaped door leaf mounts

The force is applied on both sides: To achieve this, a synchronised drive is installed. Ball-bearing precision rolling units have to be used for the precise, smooth and low-noise guidance of the hinge chains. A sufficiently dimensioned tension spring mechanism, ensuring the weight balancing of the door leaf and manual opening of the door (e.g. in the case of a power failure), is installed in the door frames, in accordance with DIN EN 12604.

Door leaf made from double-walled, thermally separated and insulated EFA-THERM® laths (100 mm), which are fixed onto hinge chains and moved vertically (i.e. up or down), surface finish is a 2-layer coating similar to RAL 9006 (White Aluminium).

The SPIRAL BODY is designed to guide the laths of the door leaf entirely without contact, and therefore without wear, and with best noise reduction possible.

Spiral form: Round spiral

The door system is equipped with a locking mechanism. An internal hand lever is used to operate the mechanism.

The DOOR is driven by a gear brake motor, which must be designed as high-frequency motor. The door positions are detected by means of non-wearing, inductive proximity switches, whereby the limits are determined electronically. Electro-mechanical limit switches are not permissible here.

**OPENING SPEED: up to approx. 0.5 m/s**

**CLOSING SPEED: up to approx. 0.3 m/s**

The **MICROPROCESSOR CONTROL** is installed along with the integrated frequency converter in a steel switch cabinet, protection class IP 65. Connection to 400V / 50 Hz power supply on-site.

The scope of delivery includes a DOOR LINE – LIGHT-LINE CURTAIN (EFA-TLG®), TÜV-certified and works precisely in the door closing line: The safety system is completely integrated and protected in the side frames and generates a very tight light-line curtain of infrared beams up to a height of 2.5 metres. Obstructions are detected without contact and the automatic closing movement is stopped immediately.

Regulations pursuant to DIN EN 13241-1 are complied with;

Heat insulation in accordance with DIN EN 12428, up to 0.54 W/m<sup>2</sup>K

Resistance to wind load in accordance with DIN EN 12424, up to class 4

Airborne sound insulation in accordance with DIN EN 7171, up to 26 dB(A)  
(values dependant on the door size and equipment)

for clear passage opening dimensions

Width = ..... mm x Height = ..... mm

**OPTIONS available for the high-speed spiral door, type “EFA-SST®-XXL Premium”:**

**Surface**

Powder coating of all visible, galvanised steel parts in a colour according to RAL \_\_\_\_\_  
(metallic colours are not available)

Special coating of the laths in a colour according to RAL \_\_\_\_\_

If steel parts as well as lath parts are coated in the same RAL colour, minor deviations in colour, which cannot be fully avoided, may occur due to the different surface structures of the materials. However, the supplier will do their best to keep deviations in colour to a minimum by altering the amount of gloss.

**Transparency / Door leaf design:**

Surcharge for sight laths with fully transparent, double-walled and thermally separated windows made of acrylic glass in GRP profiles (posts painted according to RAL 9006).